## **Patent Abstracts of Japan**

**PUBLICATION NUMBER** 

**PUBLICATION DATE** 

11268145

05-10-99

APPLICATION DATE

20-03-98

APPLICATION NUMBER

10072044

APPLICANT:

TORAY IND INC;

**INVENTOR:** 

HOSODA MOTOMU;

INT.CL.

B29D 7/00 C08J 5/18 H01G 4/18 H01G 4/22 H01G 4/32 // C08L 23/10 C08L 25/04

B29K 23:00

TITLE

ELECTRICALLY INSULATING FILM AND CAPACITOR USING THE SAME

ABSTRACT:

PROBLEM TO BE SOLVED: To improve a voltage resistance and to prolong its lifetime with a small size by forming an electrically insulating film of a polymer resin containing a polyolefin resin polymerized by using a metallocene catalyst as a main component, incorporating a specific ratio of an organic compound having a chlorine capturing performance, and setting a surface roughness to a specific value, thereby improving the voltage resistance.

SOLUTION: The electrically insulating film is formed of a polymer resin containing a polyolefin resin polymerized by using a metallocene catalyst, contained with 0.02 to 0.15 wt.% of an organic compound having a chlorine capturing capacity, and set with a surface roughness Ra to 0.03 to 0.30 μm. The metallocene catalyst is a bis-metal compound in which a metal atom is bonded to a cyclopentadiphenyl ring by a strong covalent bond or its derivative. Particularly, a compound of a structure in which a transition metal such as Zr or the like is held by a  $\pi$ -electron unsaturated cyclic compound as a metallic atom is excellent. Generally, it is used as a combination of an assistant medium of methylalmoxane or the like. As the compound having the chlorine capturing performance, an epoxy compound is particularly preferable.

COPYRIGHT: (C)1999, JPO